

**Facilities Management Department, Baroda Corporate Centre, Mumbai**
**Pre-Qualification number:- BCC/FM/SM/04**
**PRE-QUALIFICATION OF MANUFACTURERS FOR SUPPLY & INSTALLATION OF SECURITY EQUIPMENT AT BANK'S VARIOUS OFFICES/BRANCHES PAN INDIA**

Addendum/Corrigendum in the Pre-Qualification Document based on the queries received during Pre-Bid meeting held on 05.01.2022

Sr. no.	Page & Clause number	Existing Clause	Revised Clause / Addition
1	Page no. 4 & 5 -Turnover	Average Annual financial turnover of the firm during last - 3- Financial years, ending 31.03.2021, should be at least ₹ 20 Crores	Average Annual financial turnover of the firm during last - 3- Financial years, ending 31.03.2021, should be at least ₹ 20 Crores
2	Page no. 15 Annexure A point 10-Turnover	(Avg. turnover of last 3 years should not be less than 60.00 Lacs)	
3	Page no. 4 & 5	Manufacturers / Suppliers who are desirous of tendering for supply of modular furniture and fulfil the following minimum requirements shall be eligible to apply:	Manufacturers / Suppliers who are desirous of tendering for supply of security equipment and fulfil the following minimum requirements shall be eligible to apply:
4	Page no. 12-Application money	The bidder must pay application money	Bidders need not pay any application money
5	Page no. 15-Solvency Certificate	Solvency Certificate from Bank to be enclosed	Deleted. No need to furnish Solvency certificate
6	Page no. 30 & 35	Past Five Years i.e. from 2011-12 to 2016-17	Past five years i.e. from 2015-16 to 2020-21
7	Page no. 35, clause no. 10- FRRC	Storage Capacity shall be minimum 640 Litres with minimum usable internal size in mm as 1620 (h) x 670 (w) x 599 (d)	Storage Capacity shall be as stipulated by BIS extant code with minimum usable internal size in mm as 1620 (h) x 670 (w) x 599 (d)
8	Page no. 5	Agencies who are eligible to supply 6 out of 9 products mentioned in the list shall be considered for pre-qualification	Clause remains unchanged
9	Page no. 5	Manufacturers should have been empanelled with and/or having Rate Contract and/or executed works in at least 10 Scheduled Commercial Banks out of which 3 must be Public Sector Banks; for at least 5 out of 9 security Equipment as mentioned in Annexure –I.	Manufacturers should have been empanelled with and/or having Rate Contract and/or executed works (supply of security equipment) in at least 10 Scheduled Commercial Banks out of which 3 must be Public Sector Banks during last 7 years
10	Page no. 19, Annexure-B, Point no. 5	ISO Certification	Clause remains unchanged
11	Page no. 19, Annexure-B, Point no. 3	Annual Turnover - Previous three FYs. 2018-19, 2019-20, 2020-21 a) Over 50 Crores b) 20 to 50 Crores c) between 2-20 Crores	Annual Turnover - Previous three FYs. 2018-19, 2019-20, 2020-21 a) Over 50 Crores b) 30 to 50 Crores c) between 20-30 Crores
12	Page no. 20, Annexure-B, Point no. 8	Lock manufacturing by OEM for other products viz FRFC, FRRC, Data Cabinets, Filing Cabinets.	Clause remains unchanged
13	Page no. 20, Annexure-B, Point no. 10	Possession of BIS Licence prior to the RFP	Clause remains unchanged
14	Page no. 20, Annexure-B, Point no. 12	Empanelment with PSBs	Clause remains unchanged

15	Page 4 point 5	Applications by those Manufacturers who do not submit performance certificate from their previous employers are liable to be summarily rejected.	Agency has to produce performance certificate from the respective clients with financial year wise order placed/or work executed
16	Page no. 21, Annexure-B, Point no. 16	Any Single Project Work Order	
17	Page no. 22, Annexure-B, Point no. 19	Certifications from International Research & test certification Bodies ( Global )	DELETED
18	Page no. 29- Cash Safes	The safe should have an electronic lock integration, Rise alerts and communicate to the concern person mandated both during Burglary and Robbery/Hold up ( Duress )	The agency should have provision for electronic lock integration which may be required by the Bank on case to case basis.
19	Page no. 33- Safe Deposit Locker Cabinet	The key of the locker should be of Multi row pin cylinder technology which will be handed over to the customer.	The key to be handed over to the customer may also be considered as Lever Lock as recommended by BIS
20	Page no. 34- Safe cum safe deposit lockers	The safe must have an electronic lock integration, Rise alerts and communicate to the concern person mandated both during Burglary and Robbery/Hold up ( Duress )	The product should have provision for electronic lock integration which may be required by the Bank on case to case basis.
21	Page no. 36-FRRC	The FRFC must conform to IS 14562 : 2014 under all parameters as mentioned by BIS and must have a valid BIS label on the product which will be supplied to the bank branches.	The FRFC must conform to IS 14561 : 2014 & its amendments thereof under all parameters as mentioned by BIS and must have a valid BIS label on the product which will be supplied to the bank branches.
22	Page no. 37, piont no. 3- Currency Bins	Each cabinet shall have two high precision, Godrej 6-lever lock made of brass/Zinc Alloy	Currency Bins-Each cabinet shall have two high precision,6 -lever lock brass/Zinc Alloy made by OEM
23	Page no. 5 & 14	The company/vendor must not have been blacklisted by any PSU Bank nor should their name be figured in the IBA caution list. Agencies who have been blacklisted/barred by any organization during last -10- years shall be liable to be rejected.	The company/vendor must not have been blacklisted by any PSU Bank nor should their name be figured in the IBA caution list. Agencies who have been blacklisted/barred by any organization during last -10- years shall be liable to be rejected. However, their application may be considered for further evaluation, if they provide proof of having vacated the restrictions imposed by the same client honorably . Further , notarized affidavit to be furnished by the bidder in this regard.
24	Page no. 33 & 34- Lockers	Improved facia anodised finish/stainless steel for better aesthetics. No powder coated finish	Clause remains unchanged. This will not be an essential requirement but a desirable feature
25	Page no. 34- FRRC	The cabinets should be designated by type,Nominal size and IS code i.e. FR 60/ 120 & 1000/ 1300/ 1600 & IS 14203 depending upon the deed.	Clause remains unchanged
26	Page no. 29, 31, 33, 35 & 36- Safe, Strong Room Door, Lockers, FRFC, FRRC	The OEM should have an Anti-Corrosion treatment process in Place to thoroughly degrease and clean the rust and scales using appropriate chemical treatments. The process must be 100% automated.	The OEM should have an Anti-Corrosion treatment process in Place to thoroughly degrease and clean the rust and scales using appropriate chemical treatments. This will be applicable to Safe, Strong Room Doors, Safe cum Safe deposit locker. For FRRC & FRFC If agency uses anti corrosive material, evidence for having used the same to be produced.
27	Page no. 29, 31 & 33- Safes, Strong Room Door, Safe cum safe deposit locker	The safe/door should have a 3rd re-locker in addition to the 2 re-lockers recommended by BIS as an additional safety precaution.	Clause deleted
28	Page no. 29 & 34- Safe & Safe cum safe deposit locker	Under Duress attack the safe should open with a time delay.	Clause remains unchanged. This will not be an essential requirement but an additional feature
29	Page no. 29- Cash Safes	The safe should have a two-stepped construction	The safe should conform as per extant BIS guidleines/code
30	Page no. 30 -Safes	The total steel thickness across the walls of the safe shall be minimum 7 mm out of which the outer body plate shall be of minimum 5 mm thick.	The total steel thickness across the walls of the safe shall be minimum 7 mm & should confirm as per extant BIS guidleines/code

31	Page no. 30 - Safes	The thickness of door over the Bolt work should be minimum 140mm	Since the thickness varies from class to class, The safe should confirm as per extant BIS guidelines/code
32	Page no. 30- Safe	The Safe shall have two automatic relocking devices and one additional relocking system for Key lock fitted in the door which being always on guard shall come into operation if lock is dislodged by explosives or by other means	Clause remains unchanged. This will not be an essential requirement but an additional feature
33	Page no. 31, -Strong Room Door-table	Specification of different classes of Strong Room Doors Class AAA TRTL – 180 FR – 180 Burglar resistance capacity – 180 min Fire resistance capacity – 180 min Class AA TRTL – 120 FR – 120 Burglar resistance capacity – 120 min Fire resistance capacity – 120 min Class A TRTL – 60 FR – 60 Burglar resistance capacity – 60 min Fire resistance capacity – 60 min	Specification of different classes of Strong Room Doors Class AAA TRTL – 180 Burglar resistance capacity – 180 min  Class AA TRTL – 120 Burglar resistance capacity – 120 min  Class A TRTL – 60 Burglar resistance capacity – 60 min
34	Page no. 32, point no. 10- Strong room doors	Thickness of door over locks: Should be of minimum 100 mm thickness	Since the thickness varies from class to class, The safe should confirm as per extant BIS guidelines/code
35	Page no. 32, point no. 13- Strong room doors	Lock Case: Should be made up of minimum 5 mm thickness steel conforming to IS 2062 and shall have 2 step case construction covering entire jamb area	Lock Case: Should be made up of minimum 5 mm thickness steel conforming to IS 2062
36	Page no. 32, point no. 17- Strong room doors	FOOT BRIDGE: Hinged chequered steel foot bridge shall be provided to facilitate passage of trolleys etc in to the vault as specified by IS 11188 if required by customer.	FOOT BRIDGE: Hinged chequered steel foot bridge shall be provided to facilitate passage of trolleys etc in to the vault as specified by IS 11188 if required for class AAA, AA, A.
37	Page no. 32, point 18, sub point 2- Strong room doors	Provision of additional security alarm features/ timer lock could also be considered while inviting bids, depending upon Circles requirements accordingly	The product should have such provisions for additional security alarm features/ time lock for incorporation which may be required by the Bank on case to case basis.
38	Page no. 33, point no. 6- Locker	Each locker should have light which work on motion based technology during operations.	Clause remains unchanged. This will not be an essential requirement but an additional feature
39	Page no. 33, point no. 10- Locker	The provision for placing personal lock on inner face and pad lock on outer face by the customer on individual locker will be incorporated as additional facility while calling for bids	Clause remains unchanged.

40	Page no. 35, point no. 3-FRRC	The external shell of the cabinet shall be of steel of minimum 2 mm thick and internal shell of steel of 1.6 mm thick, further fortified by suitable fire resistant barriers to meet the required protection. The overall protection to the contents shall be minimum 70 mm on all six sides.	The FRRC must confirm to IS 14203 and its amendments thereof
41	Page no. 35, point no. 6-FRRC	Door: The external door of the cabinet shall be of steel of minimum 2 mm thick, further fortified with hard plate over the lock for burglary protection and fire resistant barrier material to meet required fire protection.	The FRRC must confirm to IS 14203 and its amendments thereof
42	Page no. 35, point no. -7-FRRC	Bolt work: The door shall be secured by four way locking mechanism / Bolt work with minimum 8 moving shooting bolts of 20 mm diameter	Bolt work: The door shall be secured by four way locking mechanism / Bolt work with minimum 8 moving shooting bolts of 15-20 mm diameter
43	Page no. 35, point no. 8-FRRC	FRRC- The Lock body shall be of Zinc Alloy and the Levers in the lock shall of Brass (IS 410).	Mild Steel with Zinc plating may be considered subject to meeting all requisite specification as per extant IS code 14203 and its amendments thereof
44	page no. 36-FRRC	The Lock body shall be of Zinc Alloy and the Levers in the lock shall of Brass (IS 410).	Mild Steel with Zinc plating may be considered subject to meeting all requisite specification as per extant IS code 14562 and its amendments thereof
45	page no. 36-FRRC	The minimum usable internal dimension of each drawer shall be 280mm (H) X 380mm (W) X 630 mm (D)	The minimum usable internal dimension of each drawer shall be 260mm (H) X 370mm (W) X 450 mm (D) as per extant BIS guidelines confirming to FRFC
46	Page no. 37, piont no. 3-FRRC	This can be either in 'Standard' or 'lateral' type categories	Clause remains unchanged
47	page no. 38, point no. 7-Currency Bins	The operation shall be such that only one bin shall operate at a time, hence entire quantity of valuable and cash is not exposed.	Clause remains unchanged
48	Page no. 38, point no. 9-Currency Bins	The minimum dimension of Bin cabinets (in mm) shall be....	Clause remains unchanged
49	Page no. 39, point no. 1-Gold Safe	The Gold loan safe shall have a Bolt Detent mechanism to ensure that the shooting bolts are not operated in door open condition	Clause deleted
50	Page no. 39, point no. 3-Gold Safe	The lock of the Gold loan safe door shall have mechanism which disables key withdrawal in lock open condition.	Clause deleted
51	Page no. 25, point no. 7	Self-certified letter that any maintenance / repair problem would be resolved within 48 hours	Relaxation of additional 24 hours can be considered only for areas under North East and Jammu & Kashmir
52	Page no. 30- Safe	The thickness of the Torch and Tool resistant material in the body and door of the safe shall be minimum 95 mm each	Since the thickness varies from class to class, The safe should confirm as per extant BIS guideines/code
53	Wherever mentioned in the PQ document	IS Code	All IS codes to be read including its amendments thereof
54	Page no. 39- Gold Safe	Shall be machine formed, have multi bend construction with fully welded structure without single rivet thus imparting strength and rigidity to the cabinets	Shall be machine formed, have multi bend construction with fully welded structure without single rivet thus imparting strength and rigidity to the cabinets. Also following 2 types may be considered 1. Knockdown BC 2. Fully assembled BC

55	Page no. 38 point no. 5- Currency Bins	Each cabinet shall have a hasp and staple for additional security	Clause remains unchanged
56	Page no. 39- Gold Safe	Gold Safe- Table-Sr. No. Description Features 1 AA class TRTL-60 2 BB class TRTL-15*5 3 B class TRTL-15 (D) * TL-15*5	Gold Safe- Table-Sr. No. Description Features 1 AA class TRTL-60 2 BB class TRTL-15*6
57	Page no. 38 point no. 6- Currency Bins	Shall have Flag Indicator to provide a visual indication that the cabinet is Locked : In Locked condition the Flag indicator shall be green whereas in unlocked condition, it is Red Flag	Clause remains unchanged
58	Page no. 38 point no. 7- Currency Bins	The operation shall be such that only one bin shall operate at a time, hence entire quantity of valuable and cash is not exposed	Clause remains unchanged
59	Page no. 38 point no. 2	Tangbar- The weight of a single tang bar shall be minimum 6 Kg	The weight of a single tang bar shall be minimum 5.6 Kg or as per extant RBI guidelines whichever is higher
60	Page no. 5, point no. 6	For FRRCs and FRFCs valid certification by CBRI/BIS for Fire and Burglary resistance is mandatory	For FRRC and FRFC valid standard is IS 14203 & 14561 respectively and its amendments thereof
61	Page no. 21, Annexure-B, Point no. 13	Consistency in Manufacturing Process. a) Processes Automation. .Anti-Corrosion Process .Welding process .Minor processes or no Automation. b) Quality Assurance .Incoming Inspection .In Process Inspection .Pre Dispatch Inspection All 3 stages of Q.A. Inspection Any 2 stages of Q.A. Inspection No Inspection	Consistency in Manufacturing Process. a) Processes Automation. .Anti-Corrosion Process .Welding process .Minor processes or no Automation. All 3 process available with company Any 2 process available with company Any 1 process available with company b) Quality Assurance .Incoming Inspection .In Process Inspection .Pre Dispatch Inspection All 3 stages of Q.A. Inspection Any 2 stages of Q.A. Inspection No Inspection
Other queries of vendors			
1	Mode of submission-online		All queries related uploading and submitting bid in the tender portal shall be dealt by M/s ITI ltd. Contact details shared in the pre qualification document
2	Items to be procured from GeM portal		All security products proposed to be procured through this Pre Qualification process appears to be not available in GeM portal. As such this process shall be continued for identification of agencies by Bank

**All the other terms and conditions of the tender will remain unchanged**

1. All applicants are advised to consider the above points while submitting the applications.

2. A revised data sheet is enclosed for your reference.

3. The above shall be complementary in contents with the existing terms and conditions of the PQ application except otherwise explicitly superseded. Other terms and conditions of the PQ application

shall remain unchanged.

4.This addendum shall form part of the pre qualification document . The submission of same shall be treated as acceptance of those conditions.

The last date of online submission of the PQ applications shall be 31/01/2022 upto 1500 hrs and same shall be opened on the same day @ 1530 hrs.

General Manager  
(Facilities Management, COA,PD&RD)  
BCC, Mumbai  
Date 21/01/2022