

FURNISHING WORKS OF BANK OF BARODA BRANCH/ ATM, KARAPARAMBA					
(ALTERNATE PREMISES)					
(INTERIOR FURNISHING)					
Sl.No	DESCRIPTION OF ITEMS	QTY.	UNIT	RATE	AMOUNT
<b>1</b>	<b>GYPSON BOARD WORK</b>				
	<b>FALSE CEILING:</b> Providing and fixing Gypsum board ceiling with ISI standard Gypsum board using G.I perimeter channels along the perimeter of ceiling and sides of R.C.C column, screwing to brick walls/R.C.C. surface with the help of Nylon sleeves and screws at 600mm c/c, then suspending or fixing G.I. intermediate channels at 1200mm c/c (or nearest spacing) with the help of G.I. hanger/ steel G.I. supports/G.I ceiling angles fixed to supports with G.I. cleat and steel expansion fastening, then the ceiling section fixed to the intermediate channels for fixing Gypsum sheet with the help of connecting clip and screws in both direction perpendicular to the intermediate channels at 400mm c/c at required level including cost and conveyance of all materials and labour charges, scaffolding charges, finishing the joints of the sheets with Gypsum powder paste finishing.	115.00	M <sup>2</sup>		
	Provisions for fixing the required electrical lights and fittings shall also be provided. The ceiling shall be painted with two coats Royal Luster Asian Paints paint over a coat of cement primer and putty.				
<b>2</b>	<b>TOUGHENED GLASS DOOR:</b> Providing and fixing plain (210 high) 12mm thick Toughened glass doors.				
2a)	150cm wide (210cm high) double flap <b>Toughened</b> glass door for main entry to premises with patch fitting. <i><b>*DORMA BTS 84 (Accessories to be provided shall include BTS 84 Floor Spring, SM 1001 – Top Pivot, SM 1010 – Bottom Patch, SM 1020 – Top Patch, SM 1052 E – Strike Plate, 60cm high 'H' type SS handles - XL-C 3004 A, a lock placed at the centre.)</b></i>	1	NOS.		
2b)	90cm wide <b>Toughened</b> glass door for ATM/ Manager cabin. <i><b>*DORMA BTS 84 (Accessories to be provided shall include BTS 84 Floor Spring, SM 1001 – Top Pivot, SM 1010 – Bottom Patch, SM 1020 – Top Patch, SM 1052 E – Strike Plate, 30cm high 'H' type SS handles - XL-C 3004 A, a lock placed at the centre.)</b></i>	2	NOS.		
2c)	80cm wide <b>Toughened</b> glass door for Priority cabin. <i><b>*DORMA BTS 84 (Accessories to be provided shall include BTS 84 Floor Spring, SM 1001 – Top Pivot, SM 1010 – Bottom Patch, SM 1020 – Top Patch, SM 1052 E – Strike Plate, 30cm high 'H' type SS handles - XL-C 3004 A, a lock placed at the centre.)</b></i>	1	NOS.		
<b>3</b>	<b>DOORS:</b>				
3a)	Providing and fixing flush doors (6mm marine ply on both sides over suitable frame) with laminated front and back for records, strong room and dining room. All the doors shall be provided with door closures, heavy duty brass hinges (4 nos.), godrej lock with handles and a vision panel (refer drawing).	3	NOS.		



Sl.No	DESCRIPTION OF ITEMS	QTY.	UNIT	RATE	AMOUNT
4b)	Providing and fixing in position fully glazed partition upto 210cm height using 12mm thick Toughened Glass of approved make in mply partition as specified elsewhere. The glazed portion is from 15/ 90 cm to 210/ 240cm height. Over and above 210cm height, non-glazed plywood partitions shall be provided, as instructed. (this shall be measured separately elsewhere). The glass shall be fixed securely with Aluminium glass profile of Enox glazing profile EAPS- 1032 or equivalent at bottom of the floor and inside the ceiling. The rates quoted shall be inclusive of all the fittings and other accessories. Silicon sealant shall be applied between the glass panel to make it absolutely water tight.	50.00	M <sup>2</sup>		
4c)	Providing and fixing full height double skin partition for UPS room (refer the drawing enclosed). Partition should have an overall thickness of 7.5cm and shall be provided with 12mm thick bison panel (cement sheet) board in side and 12mm BWR IS 303 ply outside of room over frame work made of 1.6mm thick 50mm x 50mm zinc coated G.I. box sections or same size 1.5mm thick aluminium sections at 60cm c/c spacing both ways and consisting of floor and ceiling flanges of suitable size which are to be fixed to ceiling/ floor with suitable anchor bolts. The boards shall be fixed to frame work with suitable screws on sections with a spacing of 30cm c/c. The joints of boards shall be such that it staggers, so as to avoid cracking. The boards shall be finished with recommended jointing compound and two coats of cement primer.	30.00	M <sup>2</sup>		
5	<b>PATRIRITION IN STRONG ROOM:</b> Fabricating & fixing a partition wall in strong room upto ceiling height as marked in lay out plan. All sides horizontal & verticals shall be powder coated aluminium sections 2½"x1½", bottom rail 4"x1½" . Partition shall be made with 18mm thick 303 Grade (BWR) plywood finished with 1 mm thick laminate on both sides.	10.00	M <sup>2</sup>		
6	<b>WRITING STAND:</b> Providing a writing desk with notice board and suggestion box. (In main Bank)	1	EACH		
7	<b>PANELLING:</b> Fixing panelling for columns in specified area upto false ceiling height using laminate over 6mm thick marine ply fixed over G.I channels (if necessary). The laminate facing shall be provided with horizontal grooves at specified intervals.	18.00	M <sup>2</sup>		
8	<b>TABLES:</b>				
8a)	Supply and fixing in position Manager's table (165cm x 75cm) and side table (120cm x 45cm) as per the enclosed sketch.				

Sl.No	DESCRIPTION OF ITEMS	QTY.	UNIT	RATE	AMOUNT
	Main working top and edges shall be made from minimum 18mm thick Marine ply finished with 1mm thick laminates of approved colour and make as per the sketch attached. Top shall be ergonomically profiled, supported on the 3- drawer pedestal on one side and shutter unit on the other side with MS powder coated studs having minimum diameter of 50mm duly powder coated. Modesty panels shall be made from minimum 15mm thick Marine ply finished with 1mm thick laminates. The Modesty panel will have a 3-piece construction comprising of 3 bands as per the dimension and color combination shown in the drawing. All exposed edges shall be lipped with minimum 2.0mm thick machine pressed PVC edge banding and other edges shall be finished with minimum 0.8mm edge banding.				
	3-Drawer Pedestal shall have an overall dimension of 300mm width x 400mm depth x 650 mm height having two small upper drawers and one bigger filing drawer at bottom. Outer casing shall be made from minimum 15mm thick Marine ply finished with 1mm thick laminates as shown in drawing supported on minimum 50 mm height MS powder coated legs made from minimum 50mm dia M.S. pipes duly powder coated and fitted with ABS plastic shoes having a concealed threaded mechanism for height adjustment.				
	The drawer movement of two smaller upper drawers shall be on full-panel drawer slides made from CRCA steel duly powder coated which will also form the sides of the drawer. Movement of these 2 drawers will be on plastic rollers. Lowermost drawer will have its sides extended all the way up to the upper level of drawer fascia. The drawer movement of this lowermost drawer will be on telescopic ball slides. Drawer backs and bottoms of all 3 drawers will be made from minimum 15mm thick Marine ply finished with 1mm thick laminates having their exposed edges lipped with minimum 0.45mm thick PVC edge banding.	1	NOS.		
	Each pedestal unit will be provided with a centralized locking mechanism comprising of a multi-drawer lock fitted in the uppermost drawer fascia. All 3 drawer fascia shall be provided with "C"-shaped stainless steel handles of minimum 96mm length.				
8b)	Supply and fixing in position officer/clerk table (140cm x 75cm) and side table (80cm x 40cm) as per the enclosed sketch. The total unit shall be finished as above.	1	NOS.		
8c)	Supply and fixing in position bank-man tables (100cm x 50cm) as per the enclosed sketch.	1	NOS.		
8d)	Providing and fixing Low Counter of 150cm (L) x 60cm (D) x 75cm (H), to be done as per drawing. Modules shall be done in Ply boxing with wire manager provision etc. and apron finished with 1mm thick frosty white laminates and orange central band (75 mm wide) and working surface top shall be finished with 1mm thick "Sunmica" or equivalent make along the front panel with an orange band or strip inserted as per drawing and as per approved brand list laminates. Counter top shall be in 18mm Mply while apron and draw unit front shall be in 15mm Mply.	9.00	RMT		

Sl.No	DESCRIPTION OF ITEMS	QTY.	UNIT	RATE	AMOUNT
8e)	Side tables (80/90 x 40cm) with same specifications as for side table in manager table	2	NOS.		
8f)	Fabrication & fixing 18mm thick marine plywood dining counter 60cm wide (at a height of 75cm from finished floor level) in position as shown in the enclosed lay out plan with suitable supports. All exposed sides to be finished with two coat enamel paint over a coat of wood primer and putty. Top of the counter should be finished with laminate.	2.50	RMT		
<b>9</b>	<b>CASH COUNTER:</b> Fabricating & fixing cash counter 150cm length, 60cm wide and 75cm height for staff side (105cm for customer side). Laminated Portion of these panels shall comprise of minimum 12mm thick laminated Mply boards having all their edges lipped with minimum 0.45mm thick PVC edging. Modules to be made in marine plywood with provision of wire manager etc. finished with 1.0 mm thk. "Sunmica" or equivalent make along the front panel with an orange band or strip inserted 15cm high in "Sunmica" make SC-G 599 / 1599 or equivalent as per approved brand list laminates. The teller counter top shall be finished with same laminate.	1.60	RMT		
<b>10</b>	<b>FABRICATING &amp; FIXING STORAGE RACKS:</b>				
10a)	Fabricating and fixing 90cm high racks with 2 compartments using 18 mm thick marine plywood finished on outer sides with 1mm thick laminates; with shutters. Shutters (15mm marine ply) to be fixed with self closing special hinges (2nos. on each shutter). 10mm thick/100mm wide laminated m/ply skirting shall be provided. Top of unit shall be laminated. Each rack should have two cabinets which are divided equally & width of each rack is to be divided equally as in sketch. Depth of the rack has to be minimum 40cm. All the shutters should be provided with good quality stainless steel handles. (Note that the back side of the rack also should be fixed with 6 mm thick marine grade plywood with lamination inside. (Inside portion shall be laminated with white laminates)	3.00	M <sup>2</sup>		
10b)	Fabricating and fixing 210/240cm high and 40cm deep racks with same specifications as above. (Each compartment shall divided equally and shall have Two shutters.)	15.00	M <sup>2</sup>		
10c)	Fa+B79:B80 fabricating and fixing 45cm wide, 210cm high and 40cm deep racks with multi-wood (specified in the attached sketch) with single door. The unit shall be wall mounted with suitable anchor bolts and "L" angles. Unit shall be initially finished with MRF vapocure paint, over which specified colour enamel paint shall be provided.	1.00	M <sup>2</sup>		
<b>11</b>	<b>ROLLER BLINDS:</b> Supply & fixing roller type blinds, including all fittings, for windows (as per the instruction of bank) including cost of all materials, labour charges etc. complete.	5.00	M <sup>2</sup>		

