Laptop

ANNEXURE - 12A

Laptop	Со	mplied
HARDWARE :- Make & Model of Laptop –	Y/N	If No. Remarks
CPU – Min. 1.9 Ghz Quad core base frequency or higher		
CHIPSET - Integrated with CPU or equivalent		
BIOS - Standard BIOS		
MEMORY - Min. 8 GB DDR4 or Higher		
MEMORY EXPANDABILITY - Expandable to Min 16 Gb with one slot free		
MEMORY SLOT - Min. 2 Nos DDR4 DIMM Slot		
HDD - Minimum 500GB (or Higher) @7200 rpm Hard Disk		
GRAPHICS – Integrated Graphics		
MULTIMEDIA - Integrated Multimedia with Built-in Audio Speakers & Microphone		
INTERFACES - Min 5 USB Ports*, RJ45, Audio Out/In, Mic In, Min 1 VGA Port & Min 1		
HDMI Port. (In case the laptop has less than 5 USB 2.0 ports, then a USB Hub with multiple	I	
USB connections (enabling 5 devices plug-in through USB port) should be provided at no	I	
extra cost)	I	
CAMERA - Built-in webcam with minimum High Definition 720p		
KEYPAD - Integrated for laptop sized (Minimum 84 Keys) Windows compatible Spill-		
resistant	I	
POINTING DEVICE - Wide Touchpad below keyboard for laptop		
EXTERNAL DEVICE - USB Mouse with scroll button(OEM)		
WIRELESS / BLUETOOTH - Should have built-in support for Bluetooth 4.0, Wi-Fi (IEEE		
802.11b/g/n) and Ethernet (10/1000 Base-T)		
COMPLIANCE (Latest) - Safety - Any one or more EPEAT Gold rating, Energy Star 5.0	I	
compliant, Green guard, RoHS & Green Peace Rating of 4 or above		
DISPLAY - Minimum 14" HD Anti-Glare (16:9)		
BATTERY – Min 40 WHR Battery pack or higher and Min. 8 hrs backup time		
AC ADAPTER - 3 pin AC Adapter (200V/50Hz)		
ACCESSORIES - Carrying case		
WEIGHT – The Weight of the Notebook PCs should be 2.4 Kg or less including Battery.	1	
SOFTWARE :-		
ANTIVIRUS - Latest Antivirus of Bitdefender / Kaspersky / Norton / F-Secure / AVG / AVAST		
/ Mcafee/ Trend Micro / Quick Heal compatible with Microsoft® Windows® 8, Microsoft®	1	
Windows® 7 (Single Licence per Notebook PC for 3 Years with AV serial key and		
installation CD)	L	
OPERATING SYSTEM - Preloaded Windows 10 Professional (Original) bundled with		
Window 10 Pro CD, Drivers CD, Recovery CD		

Monitor

ANNEXURE - 12B

	Technical Specifications	Cor	nplied
Item	Specification	Y/ N	If no. remarks
Hardware	Make & Model of Monitor –		
Size	Min. 15-16 inch or higher LED Colour Monito (1024x768 or above)		
OEM	Among the "Leaders" Quadrant in the India region in any of the previous two Quarters as published in IDC / Gartner / Frost and Sullivan report for the PC / Laptop / Monitors.		

MFP

ANNEXURE - 12C

Multi Functional Printer			nplied	
Functions Print, copy, scan		Y/ N	If no. remarks	
Hardware	Make & Model of MFP –			
Printing	Mono			
Print speed black (normal, A4)	Min 18 ppm			
Duty Cycle In Pages	3000 pages per month			
Print technology	Ink Tank			
Print quality black (best)	Up to 600 x 600 dpi			
Paper handling				
Paper handling standard/input	Two trays.One Multipurpose tray of 250-sheet input capacity and one manual feedpaper tray of Min.100 sheet input capacity			
Duplex print options	Manual			
Media sizes supported	A4, Legal Size			
Scanner Specifications				
Scaning	Color			
Optical scanning resolution	Up to 600 x 600 dpi (1200 dpi effective)			
Bit depth	24-bit			
Copier Specifications				
Copy speed (black, best quality, A4)	Min 18 cpm			
Copy resolution (black text)	Up to 600 x 600 dpi			
Connectivity				
Standard connectivity	Hi-Speed USB2.0 port			
Compatible operating systems	Microsoft®Windows®10, Microsoft®Windows®8, Microsoft® Windows® 7 and earlier versions of Windows (XP, Vista) and Linux			
Compatible Software	Compatible with Aadhar UIDAI Software / Finacle			
Catridge				
Туре	Toner catridge provided with printer should not be a Demo Catridge			

W Screen, F Light, S Gaurd

White Screen		C	Complied	
Specification	Specification Details		If no. remarks	
Hardware	Make & Model of White Screen –	_		
Size	4 X 5 ft stand mountable / wall mountable			
Accessories	Stand			
Non-Reflecting	Yes			
Opaque	Yes			

Focus Light		Complied	
Specification	Details	Y/ N	If no. remarks
Hardware	Make & Model of Focus Light –		
Capacity	60W		
Accessories	Stand, 2Mrts Wire and on/off Switch near the operator		

Surge Protector Spike		Complied	
Specification	Details	Y/ N	If no. remarks
Hardware	Make & Model of Surge Protector Spike –		
General	6 nos. of 5A sockets (4 Indian style + 2 International Style), Fuse, on/off Switch and ISO mark		

Iris Device

ANNEXURE - 12E

				/	UKE - IZE
Make & Mo	Iris Device Spec del of Iris Device:	cifications		Con	nplied
(http://www.stqc.gov.in/sites/upload_files/stqc/files/BDCS-03-08.pdf)				-	
Specifications	Stationary (mounted: wall, tripod or stand) ¹ Hand-held ² Hand-held with alignment aid ³				lf no. remarks
Iris Diameter (In pixel)		> 210	-		
Spatial Resolution Pixel Resolution	> 60% @ 4	.0 Lp/mm > 16 Pixels	s/mm		
No. of simultaneous captured eyes ⁴		2			
Viewfinder	External	Internal	External or Internal		
Capture distance	> 750 mm	> 50 mm	> 20 mm		
Capture volume (width/height/depth)	> 250x500x500mm	> 20x15x12mm	> 20x15x12mm		
Exposure time	< 15ms	< 33 ms	< 33 ms		
Imaging wavelength		700-900 nm			
Spectral Spread	Power in any 100)nm band > 35% of t	otal power		
Scan type		Progressive			
Image margins	Left & right: 0.50x iris dian		0.25x iris diameter		
Pixel depth		> 8 bits/pixel			
Image evaluation frame rate		c, continuous image	-		
Capture mode	Auto capture with built-in o	quality check (incorp considerations)	orates NIST quality		
Sensor signal to noise ratio		> 36 DB			
Connectivity ⁵	USB 2, USB-IF certified Or Networked (TCP/IP)	USB 2, USE	3-IF certified		
Power		or independent PS			
Weight	NA	< 1 kg	< 1 kg		
Dimension	<300 x 100 x 300 mm	< 220 x 200 x 100 mm	< 220 x 200 x 100 mm		
Operating	0-49C				
temperature					
Humidity	10 – 90% non-condensing				
Durability/Shock	IP54 Exempt Crown par IEC 62474:2006.07				
Safety Standard Standards	Exempt Group per IEC 62471:2006-07 FCC Class A, RoHS				
Software AP	CC Class A, ROHS Compliant with latest UIDAI Device Capture API Specifications. Linux/Windows 64 bit VDM ready certified by UIDAI				

Note:

¹Stationary: Any capture process where the device is stationary and the subject is required to position and rest himself/herself

²Hand-held: Operator operates and holds the camera and the subject is stationary.

³Alignment aid: Camera has mechanical fixture for alignment. Optical viewfinder is not considered alignment aid.

⁴Considered simultaneous if second eye is captured within 2 seconds of first eye done without moving the device

⁵Total of only 1 USB port will be available for connectivity and power

Camera

ANN	EXU	RE ·	- 12F
-----	-----	------	-------

	Camera		
Make & Model of Camera:		Complied	
(http://www.stqc.g	gov.in/sites/upload_files/stqc/files/BDCS-03-08.pdf)		
Specification	Details	Y/ N	If no. remarks
Capture Mode	Plain live capture		
Image Quality	Full Frontal (0x01) as per ISO/IEC 19794-5		
Minimum Resolution	800 x 600		
Capture Mode	Manual Capture with Auto Focus and Auto Lighting Adjustmen	it	
Sensor	>2 Mega Pixel Native		
Connectivity ¹	High Speed USB 2.0, USB-IF certified		
Lens	Fixed, SLR		
Power	Through USB/Independent PS/Lithium Ion preferred to AA/AAA batteries		
Mount	Tripod		
Operating Temperatur	0 to 50 degree Celsius		
Humidity	10 – 90%		
Safety Standard	UL		
Software API	Software API Compliant with latest UIDAI Device Capture API Specifications		
Durability / Shock	IP 54		

Note:

¹Total of only 1 USB port shall be available for connectivity and power

Finger Print Device

ANNEXURE - 12	2G
----------------------	----

	Finger Print Device			
Make & Model of Finger Print Device:		Complied		
(http://www.stqc.g	ww.stqc.gov.in/sites/upload_files/stqc/files/BDCS-03-08.pdf)			
Specification	Details	Y/ N	If no. remarks	
Capture mode	Plain live scan capture			
Image Acquisition	Setting level 31 or higher (Section 9.1 of Biometric Design			
Requirements	Standards for UID Applications V1.0)			
Image evaluation frame rate	> 3 frames/sec, continuous image capture			
Capture mode	Auto capture with built-in quality check (incorporates NIST quality considerations)			
Capture area	> 76mm x 80mm			
Connectivity ¹	USB 2, USB-IF certified			
Power	Through USB			
Dimension (W X H X				
D)	< 160mm x 160mm x 160mm			
Weight	Maximum 2.5 Kg.			
Operating				
temperature	0 – 50 C			
Humidity	10 – 90% non-condensing			
Durability / Shock	IP 54			
Standards	UL certified (if applicable). Meets ISO 19794-4:2005 Section 7 and Annex A certification requirements (IAFIS Appendix F certified).			
Stanualus	Compliant with latest UIDAI Device Capture API			
Software API	Specifications Linux/Windows 64 bit VDM ready certified by UIDAI			

Note:

¹Total of only 1 USB port shall be available for connectivity and power

GPS Device

ANNEXURE - 12H

GPS Device		Complied	
Specification	Details	Y/ N	If no. remarks
Hardware	Make & Model of GPS Device:		
General	The GPS device should be certified by UIDAI as per GPS		
	related OM 4(4)/57/122/2016/E&U-Pt		
	Note: List of approved GPS vendors are available in the		
	UIDAI website, www.uidai.gov.in		
Accessories	With all necessary required cables and accessories to		
	connect to the Laptop		