Laptop

ANNEXURE - 13A

Core-i3 Processor Laptop	Coi	mplied
HARDWARE :- Make & Model of Laptop	Y/N	If No. Remarks
CPU - Intel Core i3 - 7100U Processor @ 2.40 GHz or higher with min 3 MB L3 Cache or		
higher		
CHIPSET - Any compatible Intel Original Chipset meeting the specification below.		
BIOS - Standard BIOS		
MEMORY - 4 GB DDR4 2133 Mhz or Higher		
MEMORY EXPANDABILITY - Expandable to Min 8 GB		
MEMORY SLOT - Min. 2 Nos DDR-3 DIMM Slot		
HDD - 500GB 5.4k RPM 2.5" SATA HDD (Make - OEM) or Higher		
DVD - DVD +/-RW Super Multi Drive with double layer (External / Internal)		
NIC - 10/100/1000 Mb/s PCI Ethernet Card		
GRAPHICS – Intel HD Graphics		
MULTIMEDIA - Integrated Multimedia with Built-in Audio Speakers & Microphone		
INTERFACES - Min 5 USB Ports (2.0 / 3.0), RJ45, Audio Out/In, Mic In, Min 1 VGA Port &		
Min 1 HDMI Port. (In case the laptop has less than 5 USB 2.0 ports, then a USB Hub with		
multiple USB connections (enabling 5 devices plug-in through USB port) should be provided		
at no extra cost)		
CAMERA - Built-in Integrated 1.3 Mega Pixel Camera / 720p HD or higher		
CARD READER - Multiple Card Reader (I.e. SD / XD / PRO etc.,)		
KEYPAD - Standard Keyboard		
POINTING DEVICE - Built-in Touchpad with integrated Button & Scroll Key along with		
gestures support, two-finger scoll, zoom, pinch and pivot rotate		
EXTERNAL DEVICE - USB Mouse with scroll button(OEM)		
WIRELESS - Intel® Wireless Network Connection		
BLUETOOTH - Bluetooth 4.0 Ver. Enabled or higher		
COMPLIANCE (Latest) - Safety - Any one or more EPEAT Gold rating, Energy Star 5.0		
compliant, Green guard, RoHS & Green Peace Rating of 4 or above		
DISPLAY - 14" diagonal LED-backlit HD anti-glare (1366 x 768 Resolution or Higher)		
BATTERY – Min 4-cell Li-ion Battery pack or higher.		
AC ADAPTER - 3 pin AC Adapter (200V/50Hz)		
ACCESSORIES - Carrying case		
WEIGHT – The Weight of the Notebook PCs should be 2.4 Kg or less including Battery.		
SOFTWARE :-		
ANTIVIRUS - Latest Antivirus of Bitdefender / Kaspersky / Norton / F-Secure / AVG / AVAST / Mcafee/ Trend Micro compatible with Microsoft® Windows® 8, Microsoft® Windows® 7 (Single Licence per Notebook PC for 3 Years with AV serial key and installation CD)		
OPERATING SYSTEM - Preloaded Windows 10 Pro bundled with Window 10 Pro CD, Drivers CD, Recovery CD		

Monitor

ANNEXURE - 13B

Technical Specifications			nplied
Item	Specification	Y/ N	If no. remarks
Hardware	Make & Model of Monitor –		
Size	Min. 18.5" Wide TFT LED Colour Monitor (Make – Desktop OEM) with a compliant standard of TCO 6.0		
OEM	Among the "Leaders" Quadrant in the India region in any of the previous two Quarters as published in IDC / Gartner / Frost and Sullivan report for the PC / Laptop / Monitors.		

MFP

ANNEXURE - 13C

Multi Functional Printer		Cor	nplied
Functions	Print, copy, scan	Y/ N	If no. remarks
Hardware	Make & Model of MFP –		
Printing	Mono		
Print speed black (normal, A4)	Min 18 ppm		
First page out black (A4, ready)	As fast as less than 10 sec		
Duty cycle (monthly, A4)	Up to 8000 pages		
Recommended monthly page volume	250 to 2000		
Print technology	Laser / Inkjet (Ink Tank)		
Print quality black (best)	Up to 600 x 600 dpi (1200 dpi effective)		
Paper handling			
Paper handling standard/input	Multipurpose tray of Min. 200-sheet input capacity		
Duplex print options	Manual		
Media sizes supported	A4, Legal Size		
Scanner Specifications			
Scaning	Color		
Scan type	Flatbed		
Optical scanning resolution	Up to 600 x 600 dpi (1200 dpi effective)		
Bit depth	24-bit		
File formats	PDF; TIF; BMP; JPG		
Copier Specifications			
Copy speed (black, best quality, A4)	Min 18 cpm		
Copy resolution (black text)	Up to 600 x 600 dpi		
Copier resize	25 to 400%		
Maximum copies	Up to 99 copies		
Connectivity			
Standard connectivity	Hi-Speed USB 2.0 / 3.0 port		
Compatible operating systems	Microsoft® Windows® 10, Microsoft® Windows® 8, Microsoft® Windows® 7 and earlier version of Windows (XP, Vista) and Linux.		
Compatible Software	Compatible with Aadhar UIDAI Software		
Interfaces	RS232/Centronics/USB 2.0		
Noise	less than 64 db		
Catridge			
Туре	Toner catridge provided with printer should not be a Demo Catridge		

W Screen, F Light, S Gaurd

ANNEXURE - 13D

White Screen		C	Complied	
Specification Details		Y/ N	If no. remarks	
Hardware	Make & Model of White Screen –			
Size	4 X 5 ft stand mountable / wall mountable			
Accessories	Stand			
Non-Reflecting	Yes			
Opaque	Yes			

Focus Light		Complied	
Specification Details		Y/ N	If no. remarks
Hardware	Make & Model of Focus Light –		
Capacity	60W		
Accessories	Stand, 2Mrts Wire and on/off Switch near the operator		

Surge Protector Spike		Complied	
Specification Details		Y/ N	If no. remarks
Hardware	Make & Model of Surge Protector Spike –		
General	6 nos. of 5A sockets (4 Indian style + 2 International Style), Fuse, on/off Switch and ISO mark		

Iris Device

ANNEXURE - 13E

	Iris Device Spectodel of Iris Device:c.gov.in/sites/upload_f		CS-03-08.pdf)	Con	nplied
Specifications	Stationary (mounted: Hand-held With wall, tripod or stand) ¹ Hand-held ² alignment aid ³			Y/ N	If no. remarks
Iris Diameter (In pixel)		> 210			
Spatial Resolution Pixel Resolution	> 60% @ 4.	.0 Lp/mm > 16 Pixels	s/mm		
No. of simultaneous captured eyes ⁴		2			
Viewfinder	External	Internal	External or Internal		
Capture distance	> 750 mm	> 50 mm	> 20 mm		
Capture volume (width/height/depth)	> 250x500x500mm	> 20x15x12mm	> 20x15x12mm		
Exposure time	< 15ms	< 33 ms	< 33 ms		
Imaging wavelength		700-900 nm			
Spectral Spread	Power in any 100	nm band > 35% of t	otal power		
Scan type	1 (10 : 11 0 50 :: 1:	Progressive	0.05 :: 1: 1		
Image margins	Left & right: 0.50x iris dian	•	0.25x iris diameter		
Pixel depth Image evaluation		> 8 bits/pixel			
frame rate	> 5 frames/sec	c, continuous image	capture		
Capture mode	Auto capture with built-in c	quality check (incorp	orates NIST quality		
Sensor signal to noise ratio		> 36 DB			
Connectivity ⁵	USB 2, USB-IF certified Or Networked (TCP/IP)	USB 2, USE	3-IF certified		
Power		or independent PS	I . 4 I		
Weight	NA	< 1 kg	< 1 kg < 220 x 200 x 100		
Dimension	<300 x 100 x 300 mm	< 220 X 200 X 100 mm	mm		
Operating	0-49C				
temperature Humidity	10 – 90% non-condensing				
Durability/Shock	IP54				
Safety Standard	Exempt Group per IEC 62471:2006-07				
Standards	FCC Class A, RoHS				
Software AP	Compliant with latest UIDAI Device Capture API Specifications. Linux/Windows 64 bit VDM ready certified by UIDAI				

Note:

¹Stationary: Any capture process where the device is stationary and the subject is required to position and rest himself/herself

²Hand-held: Operator operates and holds the camera and the subject is stationary.

³Alignment aid: Camera has mechanical fixture for alignment. Optical viewfinder is not considered alignment aid.

⁴Considered simultaneous if second eye is captured within 2 seconds of first eye done without moving the device

⁵Total of only 1 USB port will be available for connectivity and power

Camera

ANNEXURE - 13F

	Camera			
Make & Model of Camera:		Co	Complied	
(http://www.stqc.g	ov.in/sites/upload_files/stqc/files/BDCS-03-08.pdf)			
Specification	Details	Y/ N	If no. remarks	
Capture Mode	Plain live capture			
Image Quality	Full Frontal (0x01) as per ISO/IEC 19794-5			
Minimum Resolution	800 x 600			
Capture Mode	Manual Capture with Auto Focus and Auto Lighting Adjustmer	nt		
Sensor	>2 Mega Pixel Native			
Connectivity ¹	High Speed USB 2.0, USB-IF certified			
Lens	Fixed, SLR			
Power	Through USB/Independent PS/Lithium Ion preferred to			
rowei	AA/AAA batteries			
Mount	Tripod			
Operating Temperatur	0 to 50 degree Celsius			
Humidity	10 – 90%			
Safety Standard	UL			
Software API	Compliant with latest UIDAI Device Capture API Specifications	S		
Durability / Shock	IP 54			

Note:

¹Total of only 1 USB port shall be available for connectivity and power

Finger Print Device

ANNEXURE - 13G

	Finger Print Device		
Make & Model of Finger Print Device:(http://www.stqc.gov.in/sites/upload_files/stqc/files/BDCS-03-08.pdf)		Complied	
Specification	Details	Y/ N	If no. remarks
Capture mode	Plain live scan capture		
Image Acquisition Requirements	Setting level 31 or higher (Section 9.1 of Biometric Design Standards for UID Applications V1.0)		
Image evaluation frame rate	> 3 frames/sec, continuous image capture		
Capture mode	Auto capture with built-in quality check (incorporates NIST quality considerations)		
Capture area	> 76mm x 80mm		
Connectivity ¹	USB 2, USB-IF certified		
Power	Through USB		
Dimension (W X H X			
D)	< 160mm x 160mm x 160mm		
Weight	Maximum 2.5 Kg.		
Operating			
temperature	0 – 50 C		
Humidity	10 – 90% non-condensing		
Durability / Shock	IP 54		
Standards	UL certified (if applicable). Meets ISO 19794-4:2005 Section 7 and Annex A certification requirements (IAFIS Appendix F certified).		
Software API	Compliant with latest UIDAI Device Capture API Specifications Linux/Windows 64 bit VDM ready certified by UIDAI		

Note:

¹Total of only 1 USB port shall be available for connectivity and power

GPS Device

ANNEXURE - 13H

GPS Device		Complied	
Specification Details		Y/ N	If no. remarks
Hardware	Make & Model of GPS Device:		
General	The GPS device should be certified by UIDAI as per GPS related OM 4(4)/57/122/2016/E&U-Pt Note: List of approved GPS vendors are available in the UIDAI website, www.uidai.gov.in		
Accessories	With all necessary required cables and accessories to connect to the PC/Laptop		